

X800

PORTABLE POS SYSTEM



- Dedicated merchant and customer displays for seamless interaction
- High-speed transaction processing
- Multiple communication options



RESTAURANT



HOTEL



CONVENIENCE STORE



RETAIL



SMALL MERCHANT

OS	Android 10.0		
Processor	AP: Octa-Core Cortex A53, 1.8GHz SP: Arm Cortex M3 security core		
Memory	2GB LPDDR4+16GB eMMC 4GB LPDDR4+64GB eMMC MicroSD card slot up to 256GB	Optional	
Main Display	8-inch portrait IPS display, resolution of 800 x 1280, capacitive multi-touch screen		
Customer Display	5-inch landscape IPS display, resolution of 800 x 480, capacitive multi-touch screen		
Wireless Communication	4G / 3G / 2G Wi-Fi (802.11 a/b/g/n/ac) 2.4G&5G Bluetooth 2.1 EDR/3.0 HS/4.2 LE		
Positioning	GPS/BEIDOU/GLONASS/GALILEO/QZSS/SBAS		
Magnetic Card Reader	Triple track, bi-directional, conforming to ISO 7810/7811/7813		
Smart Card Reader	EMV L1/L2, conforming to ISO 7816, 1.8V/3V/ 5V, synchronous & asynchronous, T=0 & T=1		
Contactless Card Reader	EMV Contactless L1, conforming to ISO 14443 Type A/B, Mifare , Felica		
Camera	2 MP fixed focal front camera, support 1D/2D code payment 2 MP fixed focal rear camera, support 1D/2D code payment		
Audio	1 x Speaker, 1 x Microphone, 1 x Audio JACK, support audio recording and media play		
Keypad	Secure virtual keypad for PIN entry, 1 x power button		
Printer	High-speed thermal printer, 80mm/s	Paper roll diameter: 50mm	Paper width: 58mm
Battery	Li-ion battery, 3.8V/6000mAh/22.8Wh		
Peripheral Ports	1 x Type-C, USB2.0 OTG Pogo Pins		
Card Slots	2 x SIM, 1 x SAM, 1 x SD 1 x SIM, 2 x SAM, 1 x SD	Optional	
	1 x SIM, 2 x SAM, 1 x SD, 1 x ESIM	Optional	
Power Supply	Input: 100-240V AC 50/60Hz	Output: 5.0V DC, 3A	
Dimensions	274.9mm(L)*123.4mm(W)*101.6mm(H)		
Weight	895g including battery		
Docking Station	Charging base: Pogo Pins for charging Multi-functional base: 2 x USB-A, 1 x Type-C (Power), 1 x Ethernet (RJ45), 1 x Cash drawer port, Pogo Pins for charging	Optional	
Expansion HUB	1 x RS232, 2 x USB-A, 1 x Type-C, 1 x Ethernet (RJ45), 1 x Cash drawer port	Optional	
Environment	Operating temperature: -10°C~50°C (14°F~122°F) ① Storage temperature: -20°C~60°C (-4°F~140°F) Relative humidity: 5%~95% (Non-condensing)		
Certifications ^②	PCI PTS 6.x, EMV L1/L2, EMV Contactless L1, PayPass, payWave, American ExpressPay, Discover D-PAS, UnionPay QuickPass, JCB, TQM, CE, RoHS, CB, FeliCa, MIC, BIS, Rupay, MCCS, Saber, WEEE & VOC, FCC		



Compact size and ergonomic form factor for optimized usage.



Intuitive card insertion and swipe for both customer and merchant.



Large paper reel for high transaction volumes.



Optional docking station with rich peripherals, Placement flexible



Newland Payment Technology

©2025 Fujian Newland Payment Technology Co.,Ltd. All rights reserved.
Please be aware that all features and specifications are subject to change without prior notice.

 **Newland NPT**