


# N950

## FLAGSHIP ANDROID SMARTPOS



With ground-breaking design and user-friendly ergonomics, N950 sets a new benchmark for Android SmartPOS terminals. Leveraging a state-of-the-art processor and high-performance chipset, N950 allows business users to seamlessly combine point-of-sale and value-added services with fast payment acceptance, by card or mobile wallet. Customer engagement takes on a whole new dimension.



MALL



RESTAURANT



HOTEL



AIRPORT



STADIUM

OS	Android 12	●
Processor	AP: Cortex Quad-core A53, 2.0GHz SP: ARMv7-M security core	●
Memory	2GB RAM, 16GB FLASH 3GB RAM, 32GB FLASH 4GB RAM, 64GB FLASH MicroSD card slot up to 256GB	Optional Optional ●
Display	5.99-inch TFT full color LCD display, resolution of 1440 x 720, with adjustable backlight, capacitive multi-touch screen, support electronic signature	●
Wireless Communication	4G / 3G / 2G	●
Positioning	Wi-Fi (802.11 a/b/g/n/ac) 2.4G&5G, Bluetooth 2.1/5.0	●
Magnetic Card Reader	GPS/GLONASS/BEIDOU/Galileo	●
Smart Card Reader	Triple track, bi-directional, conforming to ISO 7810/7811/7813	●
Contactless Card Reader	EMV L1/L2, conforming to ISO 7816, 1.8V/3V/ 5V, synchronous & asynchronous, T=0 & T=1	●
	EMV Contactless L1, conforming to ISO 14443 Type A/B, Mifare , Felica	●
	0.3 MP front camera, support 1D/2D code payment	●
Camera	2 MP front camera, support 1D/2D code payment 5 MP autofocus rear camera with flashlight, support 1D/2D code payment 8 MP autofocus rear camera with flashlight, support 1D/2D code payment Professional code scanner, NLS-N1, hardware decoding, support 1D & 2D code payment Note: The rear camera and scanner cannot be used simultaneously as they are mutually exclusive features.	Optional ● Optional Optional ●
Audio	1 x Speaker, 1 x Microphone, support audio recording and media play	●
Keypad	Secure virtual keypad for PIN entry, 1 x power button, 1 x VOL+, 1 x VOL-	●
Printer	High-speed thermal printer, 80mm/s	●
Peripheral Ports	Paper roll diameter: 40mm	●
Card Slots	Paper width: 58mm 1 x Type C port	●
	2 x SIM, 2 x SAM, 1 x SD	●
	1 x SIM, 3 x SAM, 1 x SD, 1 x eSIM	Optional
Battery	1 x Li-ion battery, 7.2V/2600mAh/18.7Wh (Equal to 3.6V/5200mAh) 1 x Li-ion battery, 7.2V/3300mAh/23.7Wh (Equal to 3.6V/6600mAh)	● Optional
Power Supply	Input: 100-240V AC 50/60Hz	●
Docking Station	Output: 5.0V DC, 2.0A	Optional
Expansion HUB	Charging base	●
Dimensions	RS232 (RJ12/RJ11), 2 x USB-A, Type-C, Ethernet (RJ45)	Optional
Weight	201mm (L) *79.8mm (W) *62mm (H)	●
	464g including battery	●
Environment	Operating temperature: -10°C~50°C (14°F~122°F) ① Storage temperature: -20°C~60°C (-4°F~140°F)	● ●
	Relative humidity: 5%~95% (Non-condensing)	●
Certifications <sup>②</sup>	① Charging below 0°C is not recommended as it will affect battery performance. PCI PTS 6.x, EMV L1/L2, EMV Contactless L1, PayPass, payWave, American ExpressPay, Discover D-PAS, UnionPay QuickPass, JCB, TQM, CE, RoHS, MCCS, CB, Interac, ATEX	● ●



Best-in-class design and advanced ergonomics.



Unprecedented processing power and performance.



Professional barcode scanning module embedded to read 1D/2D codes quickly and accurately.



Newland Payment Technology

©2025 Fujian Newland Payment Technology Co.,Ltd. All rights reserved.  
Please be aware that all features and specifications are subject to change without prior notice.

 **Newland NPT**